


3M™ Fire Protection Products
Full Line Brochure



Confidence Even Under Fire





3M

Table of Contents

Progress & Trends	4–5
Partnership, Training & Testing	6–7
Through-Penetration Firestops	8–18
Residential & Non-Rated Fireblocks & Acoustic Sealants	19
Construction Joint Firestops	20–21
Flexible Wrap Fire Protection	22–24
Ordering Information	25–30
Online Resources	31



Protecting Lives for More Than 30 Years

In 1974, the movie *Towering Inferno*[†] sparked the imagination of Richard Licht, a 3M product developer who passionately believed 3M technologies could be used to improve the safety of multi-story buildings. Several devastating fires — including the 1980 MGM Grand Hotel fire that killed 84 people and injured 679 — inspired Licht to develop the first firestop products based on existing 3M intumescent technology.


Recognized by many as “one of the fathers of firestopping,” Licht also helped develop some of the first firestop requirements in commercial building codes. He worked tirelessly to make the codes more progressive to improve the safety of all buildings.

[†] Produced by Irwin Allen

3M Firestopping Progress & Trends

As an industry leader, 3M drives technologies that enable lower cost building solutions. For instance, 3M intumescent technology enabled the use of plastic pipes that were previously banned in commercial buildings due to their combustible nature — providing a cheaper, easy-to-install solution for electrical conduits and plumbing lines.

From Understanding Your Needs to Providing the Solution





Leadership You Can Trust

3M is proud to be the industry leader in firestopping. Our dedication to stringent testing and code developments help make buildings safer today than they were even 10 years ago. And when that dedication is backed by a brand as powerful as 3M, you get what you would expect — proven reliability and outstanding service.

The construction industry is increasingly moving toward easy-to-use firestop solutions. That's why 3M, in its leadership role, provides cutting-edge and fully integrated systems. These systems are designed to help you efficiently construct safer buildings that help protect lives and property.

The majority of 3M's firestopping innovations are tested in the company's own UL and Intertek certified fire-test center. By testing these systems in job-specific conditions, 3M can more effectively provide fire protection solutions that meet current industry needs.

Comprehensive fire protection includes fire detection, fire containment and fire suppression. 3M™ Fire Protection Products address fire containment and are an integral part of a well-designed fire protection system. Our understanding of the spread of fire, smoke and toxic gases helps us continue to create preventative and affordable firestopping solutions.

Building designs and uses continue to evolve, and so too must 3M firestop technology. For example, in buildings where telecommunication cables are constantly being upgraded, the 3M™ Fire Barrier Pass-Through Device allows for re-enterability and helps keep cables organized and protected.

From time-tested fire barrier sealants to today's innovative firestop devices and duct wraps, 3M scientists work to develop solutions to firestop virtually anything on a building site. With over 100 products and almost 1,000 tested approved systems, 3M has the most complete program for all of your firestopping needs.



Partners in Protection

Being a leader in fire protection goes beyond selling innovative products. 3M partners with you from the start — providing a comprehensive library of tested and listed systems, excellent technical services and the superior training you need to enhance your firestopping capabilities.

We meet with you to discuss your application needs and to help you select the best firestopping solutions. To help ensure your inspection process goes smoothly, we work directly with building inspectors. By continuing to work closely with you throughout a building's life — including retrofit and maintenance activities — we support you as you work to ensure your building's firestopping is being properly managed.

Risk Management and Facility Maintenance

3M™ Firestop Risk Management and Facility Maintenance Programs provide a comprehensive approach to helping you manage the complexities of the firestopping process. From helping you define your initial needs to helping manage your firestopping throughout a building's life, we walk you through the decisions and steps required to keep your project on time, in budget and code-compliant. Our Healthcare Facility Maintenance Program includes additional tools for Joint Commission and other critical life safety inspections.

For more information regarding the 3M Firestop Risk Management and Facility Maintenance Programs, contact your local 3M Fire Protection Sales Representative, or call 1-800-328-1687.



3M™ Firestopping Partnership

Choosing a System

The easy-to-use, online 3M™ Firestop Systems Selector helps you choose the firestop solution best suited to your application. To learn more, and to see the latest in firestopping solutions, visit www.3M.com/firestop



Training With The Best

When it comes to training, 3M delivers. We provide comprehensive firestop training online through our exclusive e-Train program, so you can train when it's most convenient, 24/7.

e-Train provides a wealth of information — from firestopping basics and system nomenclature to detailed installation techniques. The program's high-quality videos highlight proper installation techniques in a broad range of systems for through penetrations, construction joints and flexible wrap systems.

Over the last 10 years, 3M has provided detailed, hands-on firestop training for more than 5,000 code officials, architects, contractors and firestop professionals at our fire-test center. Plus, 3M offers jobsite and on-location training by our qualified sales representatives.

For more information, visit www.3M.com/firestop



o, Training & Testing

3M™ Test Center

For more than 20 years, our fire-test center has ensured quality results and has been qualified under UL and Intertek guidelines for UL's Client Test Data Program and Intertek's Satellite Laboratory Program. Extensive product testing, online and hands-on training are just a few more ways 3M partners with you to help keep people safe.



Through-Penetration Sealants & Foam



Through-Penetration Firestops

Easy-to-install fire barrier products designed to take the guess work out of firestopping where mechanical, electrical or plumbing penetrations pass through fire-rated floors and walls.



3M™ Fire Barrier Sealant CP 25WB+

Our most popular intumescent firestop sealant with over 600 tested and listed systems.

- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- Superior adhesion — bonds to concrete, metals, wood, plastic and cable jacketing
- Extensive library of UL Classified fire protection systems
- Intumescent — expands when heated to seal around items exposed to fire
- Low VOC*



Check UL directory. Not approved for use with CPVC pipes made using Noveon® resins.

SOUND BARRIER

STC 57
In STC 57-rated wall assembly

FIRE BARRIER

F RATED
UP TO 2 HOURS

SMOKE SEAL

L RATED
Meets Air Leakage Requirements

ULC LISTED

TEMPERATURE

T RATED
UP TO 1 HOUR

FILL VOID OR CAVITY MATERIAL

CLASSIFIED

UL

FILL VOID OR CAVITY MATERIAL FOR USE IN THROUGH-PENETRATION FIRESTOP SYSTEMS SEE UL FIRE RESISTANCE DIRECTORY 5016

3M™ Fire Barrier Rated Foam FIP 1-Step

Innovative firestop foam that is a UL listed and rated alternative to mineral wool, bricks and runny, ineffective foams.

- One step — less product to order, keep track of and haul around
- Meets the intent of International Building Code for passive fire protection
- Broad range of applications
- One side — complete some installations from one side of the opening
- Expands at a controlled and consistent pace



3M™ Fire Barrier Sealant IC 15WB+

Cost-effective, general-purpose intumescent firestop sealant.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- CPVC compatible
- Expanded UL Classified fire protection systems
- Superior adhesion — bonds to concrete, metals, wood, plastic and cable jacketing
- Intumescent — expands when heated to seal around items exposed to fire
- Low VOC*



* 3M™ Fire Barrier Sealants, Putty and Sprays meet the intent of LEED® NC-EQ Credit 4.1 for Low-Emitting Materials. Adhesives and sealants contain <250 g/L VOC content (less H₂O and exempt solvents).

Through-Penetration Sealants



3M™ Fire Barrier Sealant FD 150+

Economical firestop sealant for through-penetration and joint applications.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Up to 4-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Easy installation, cleanup and disposal
- Sag-resistant
- Low VOC*



Available Colors:



Through-Penetration Watertight Sealants

3M™ Fire Barrier Water Tight Sealants achieve the benefits of firestopping and a water tight seal in one application, and offer the following benefits:

- Meet UL Water Leakage Test, W-rating — Class 1 requirements for systems tested and listed in accordance with ANSI/UL 1479
- Provide excellent adhesion on most construction surfaces, including concrete, gypsum, metal, plastic (CPVC compatible), wood and insulation
- Ideal for the following interior construction voids: blank openings, metallic pipes, non-metallic pipes, cables, cable trays, insulated pipes, busways, HVAC vents and ducts, combos and bottom of wall construction joints
- Low VOC*



3M™ Fire Barrier Water Tight Sealant 1000 NS

Non-slumping silicone firestop for wall and floor applications.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Up to 3-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)



3M™ Fire Barrier Water Tight Sealant 3000 WT

High-performance intumescent silicone achieves the benefits of a firestop and watertight seal.

- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- Excellent weatherability — ideal for fast-track construction
- Cures upon exposure to atmospheric humidity
- Re-enterable and repairable
- Fungal growth inhibited in the product per ASTM G 21



3M™ Fire Barrier Water Tight Sealant 1003 SL

Self-leveling silicone firestop for floor applications.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Up to 3-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)

* 3M™ Fire Barrier Sealants, Putty and Sprays meet the intent of LEED® NC-EQ Credit 4.1 for Low-Emitting Materials. Adhesives and sealants contain <250 g/L VOC content (less H₂O and exempt solvents).

Through-Penetration Devices & Kits

3M™ Fire Barrier Devices and Kits offer effective, code-compliant solutions for the firestopping of penetrating items through rated walls and floors. During a fire, 3M™ Fire Barrier Devices and Kits intumesce to form a firestop seal, which helps protect against the spread of fire, smoke and toxic gases from one room or floor to another.

3M offers pass-through and putty sleeve options for new and retrofit wall and floor applications, as well as cast-in place options for poured concrete floors.


3M™ Fire Barrier Pass-Through Devices

Re-enterable cable protection.

- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- Available sizes: 2 in. round, 4 in. round and 4 in. square
- UL classified L-rating, Smoke Seal (when used in conjunction with 3M™ Fire Barrier Moldable Putty)
- Hinged for easy retrofit installation around cables
- Mounting brackets accessories available for wall or floor installations
 - Single mounting brackets (all models)
 - Triplex and sixplex brackets for stacking multiple devices (4 in. square only)



Through-Penetration Devices & Kits



3M™ Fire Barrier Putty Sleeve Kits

An affordable and re-enterable solution to meet firestop code for the installation of cable and blanks in both new or retrofit applications.

- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- Ready-to-install kit for cable or blank firestop installations
- Blank sleeve (0% cable fill) accommodates future cable installations
- Two-piece split/hinged design for easy retrofit installation on existing cables
- Suitable for installation in gypsum wallboard and concrete walls or floors
- No gasket required

Cable types can be a mixture of the following:

- 100 pr. No. 24 AWG copper conductor telephone cables
- 1/C-750 kcmil copper conductor power cable
- 7/C-No. 12 AWG copper conductor control cables
- Coaxial cables
- 3/C-No 2/0 AWG aluminum conductor SER cable with No. 1 AWG aluminum ground conductor
- No. 23 AWG Category 6 data cables
- Fiber optic cable



Each ready-to-install kit includes everything you need for a complete cable or blank firestop installation.



Label holds sleeve together until you need to retrofit around existing cables. Slit label to open sleeve. Close the two halves around the cables.



Bracket covers oversized openings (up to 3/4 in. annular space). Innovative sleeve design assembles with the brackets to help prevent slipping during installation.



Installation of putty and application of identification label completes pass-through firestop. Putty holds cables in position, helping to prevent cable slippage and movement.

Through-Penetration Cast-In Devices

Devices designed to make firestopping through concrete easy and affordable. 3M™ Fire Barrier Cast-In Devices are installed prior to the concrete pour (attaching directly to the wood forms or fluted metal decking) and can be adjusted to various concrete depths.

3M™ Fire Barrier Cast-In Devices

Firestop devices used with metal, plastic, insulated pipes and cables.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Attach directly to wood forms or metal decking before concrete is poured, penetrating item is passed through device after the concrete cures
- Easily adjustable bodies that can be adapted to concrete height (from 2-1/2 in. to 8 in. — thicker pours accommodated with height adapter)
- Available in 2 in., 3 in., 4 in. and 6 in. diameter by 8 in. height
 - Metallic devices (black cap) are used for metallic pipe, single and multiple cables, insulated pipe and HVAC line sets
 - Non-metallic devices (white cap) are used for non-metallic pipe (including CPVC) and HVAC line sets



3M™ Fire Barrier Cast-In Metal Deck Adapter

One-piece plastic body assembly to accommodate fluted metal decks.

- Use in conjunction with 3M™ Fire Barrier Cast-in Devices
- Available for use with 2 in., 3 in., 4 in. and 6 in. 3M™ Fire Barrier Cast-In Devices



3M™ Fire Barrier Cast-In Device Height Adapter

One-piece plastic body assembly allows 3M™ Fire Barrier Cast-in Devices to be used in up to 12 in. concrete thickness.

- Designed to accommodate pipe sizes from 1-1/2 in. to 6 in.
- Easily snaps into place — no additional fastening required
- Available for use with 2 in., 3 in., 4 in. and 6 in. 3M™ Fire Barrier Cast-In Devices



3M™ Fire Barrier Cast-In Tub Box Assembly

Fastens to a 2 in. metallic 3M™ Fire Barrier Cast-In Device and creates a void for plumbing access.

- 2 in. or 3 in. foam insert depending on desired depth of access void
- Easily snaps into place and then attaches directly to wood forms
- Accommodates 1-1/2 in. and 2 in. pipe



3M™ Fire Barrier Cast-In Aerator Adaptor

One-piece plastic body assembly used to create a void around aerators.

- For use with 4 in. metallic or non-metallic 3M™ Fire Barrier Cast-In Devices



Through-Penetration Mortar

3M™ Fire Barrier Mortar

Lightweight, endothermic firestop that is ready for mixing with potable water. Firestops penetrations passing through fire-rated floor or wall assemblies.*

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Variable mix ratio permits self-leveling as well as trowelable application consistencies
- UL listed systems (including concrete floors with 2-1/2 in. minimum thickness)
- Excellent adhesion — bonds to concrete, metals, wood, plastic and cable jacketing
- Re-enterable/repairable with common trade tools
- Acts as a heat sink, reducing the likelihood of combustible matter igniting on the unexposed side of the assembly
- Dry mix available in 5 gallon (28 lbs.) pails and 44 pound bags

*Not load bearing.



Through-Penetration Packing Material

A light-weight packing material approved for use in all of 3M's UL listed through-penetration firestop systems. 3M™ Fire Barrier Packing Material is ideal for use around metallic, non-metallic, insulated pipe, HVAC, power cable and communication cable penetrants — a long-awaited alternative to mineral wool, fiberglass or backer rod.

3M™ Fire Barrier Packing Material PM 4

Lightweight packing material for use in up to 4-hour through-penetration firestops.

- Convenient, hand-tear dispensing
- Approved for use in all of 3M's UL listed through-penetration firestop systems
- 1/2 in. x 4 in. x 20.5 ft. roll (28 cu. ft.)



Through-Penetration Specialty Products

Code-approved, UL listed products that help round out 3M's comprehensive offering of through-penetration firestops.

3M™ Fire Barrier Tuck-In Wrap Strips and Rolls

Quick and easy! Eliminates the need for retaining collars, concrete screws, ladders, and other materials often required for bottom-side installations of plastic pipe.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Non-metallic listed applications include PVC, ccPVC, RNC and FRPP piping systems and HVAC line sets in concrete floor assemblies and concrete or gypsum wallboard assemblies (not for use with CPVC)
- Available in 8 ft. roll which can be cut to length for larger sized (up to 8 in.) combustible piping penetrations and in 3 sizes of precut strips for nominal plastic pipe sizes of 2 in., 3 in. and 4 in.



Simplified top-side installation and labor savings!



Gently Wrap 3M™ Fire Barrier Tuck-In Wrap Strip around pipe, over floor opening, and adhere label to adjacent side of foam strip.




Slide wrap strip downward into concrete floor to fill gaps. Once installed, wrap strip should be seated slightly below concrete floor surface.



Follow wrap installation with layer of 3M™ Fire Barrier Sealant CP 25 WB+, IC 15 WB+, or 3000 WT to create seal that meets code; fire-rated to 3 hours.

Note: Follow system details

Through-Penetration Specialty Products



3M™ Fire Barrier Ultra Plastic Pipe Devices

Firestops penetrating items such as plastic pipe and cables in new and retrofit installations.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- One-piece construction makes installation easy
- Proven technology — intumescent action quickly seals around the penetrating item in a fire
- Can be used to seal the following plastic pipes: ccPVC, PVC, FRPP, PVDF, ccABS and ABS
- Available in 1-1/2 in., 2 in., 3 in., 4 in. and 6 in. sizes*
- Ultra-fast anchoring system secures the device to most substrates without power tools (3M™ Ultra Fast Anchors sold separately)



* All sizes with the exception of the 6 in. device utilize Ultra GS intumescent material. The 6 in. plastic pipe device utilizes FS-195+ intumescent material.

Through-Penetration Specialty Products



3M™ Fire Barrier Self-Locking Pillows

Self-contained, highly-intumescent pillows designed to firestop a wide variety of through penetrations including cable trays, conduit and blank openings. Interlocking strips hold pillows securely together yet release easily for retrofit or reuse — just remove and reinstall pillows as needed.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- UL listed systems with openings up to 1,080 sq. in.
- No wire mesh reduces safety issues
- Easy to install, easy to remove and reuse
- Lock pillows together, compress and place (use 3M™ Fire Barrier Moldable Putty+ in voids to ensure proper seal)
- No graphite
- Excellent aging properties
- Pillows can be field-cut when needed
- Available sizes: 2 in. x 4 in. x 9 in. (small), 2 in. x 6 in. x 9 in. (medium) and 3 in. x 6 in. x 9 in. (large)

3M™ Fire Barrier Pillows and Self-Locking Pillows meet the intent of LEED® NC-EC Credit 4.1 for Low-Emitting Materials. Adhesives and sealants contain <250 g/L VOC content (less H₂O and exempt solvents per SCAQMD Rule 1168).

Multiple pillow sizes and ability to field-cut allow for a secure fit in most openings (seal cut edges with polypropylene box sealing tape).



3M™ Fire Barrier Pillows

Self-contained, highly-intumescent firestop pillows are stackable and conformable for new and retrofit projects.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- UL listed systems with openings up to 1,080 sq. in.
- No wire mesh or graphite
- Excellent aging properties
- Available sizes: 2 in. x 4 in. x 9 in. (small), 2 in. x 6 in. x 9 in. (medium) and 3 in. x 6 in. x 9 in. (large)

Through-Penetration Specialty Products



3M™ Fire Barrier Composite Sheet CS-195+

Ideal for firestopping blank openings and through-penetrations of multiple cables, pipe ducts, bus ducts and cable trays.

- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- No mixing or damming required
- Easy to install using common trade tools
- Easy to fasten, bolt punch or drill through (mounts easily with self-tapping screws or anchor bolts)
- Re-enterable
- Bottom-of-floor applications available
- Low VOC
- Available sizes: 16 in. x 28 in., 36 in. x 24 in., 36 in. x 36 in., 36 in. x 41 in. and 28 in. x 52 in.



3M™ Fire Barrier Moldable Putty MP+ Stix and Pads

Designed to firestop a wide variety of through penetrations, including cable, conduit, insulated pipe and metal pipe.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Provides cold smoke seal (L-rating)
- Pliable — can form into almost any desired shape
- Will not dry out or crumble — can be sealed for reuse
- Available in 1/10 in. thick pads: 4 in. x 8 in., 7 in. x 7 in. and 9.5 in. x 9.5 in. sizes
- Available stix sizes: 1.45 in. x 6 in. and 1.4 in. x 11 in.



3M™ Fire Barrier Sealants, Putty and Sprays meet the intent of LEED® NC-EQ Credit 4.1 for Low-Emitting Materials. Adhesives and sealants contain <250 g/L VOC content (less H₂O and exempt solvents per SCAQMD Rule 1168).

Pads are typically used as a wall opening protective to meet building requirements, for protection of membrane penetrations made by listed steel or non-metallic electrical boxes.


Stix are typically used to seal gaps between cables in multiple penetrations (including fiber optic inner duct) and to firestop cable bundles, insulated pipe, electrical conduit, metal pipe and other through penetrations.

Through-Penetration Specialty Products

3M™ Fire Barrier Silicone Sealant 2000+

Bonds to most common construction materials to form a flexible firestop seal.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Up to 4-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Superior adhesion
- Remains elastomeric
- Weather-resistant



3M™ Fire Barrier Wrap Ultra GS

Flexible, intumescent wrap strip expands when exposed to high temperatures.

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Excellent weatherability
- For use in drain, waste, vent or closed pipe systems
- Easily cut and shaped with common tools
- Used to firestop the following plastic pipes: ccPVC, PVC, FRPP, PVDF, ccABS and ABS
- Provides a smoke seal when used in conjunction with 3M™ Fire Barrier Sealant (CP 25WB+, IC 15WB+, 3000 WT) or 3M™ Fire Barrier Moldable Putty MP+



3M™ Fire Barrier Wrap Strips FS-195+

A one-part, intumescent strip with foil on one side.

- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- Can be cut to fit irregular shapes
- Used with the 3M™ Fire Barrier RC-1 Restricting Collar and/or 3M™ Fire Barrier Sealant for “in-hole” applications
- Use for firestopping metallic pipes, non-metallic pipes, insulated pipes and cable bundles
- 24 in. x 2 in. strips

3M™ Fire Barrier RC-1 Restricting Collar

Works in conjunction with 3M™ FS-195+ Wrap/Strip or 3M™ Interam™ Ultra GS to firestop plastic pipes up to 10 in. in diameter.

- 28 gauge steel
- Convenient 25 ft. roll — cut only what you need

Residential & Non-Rated Fireblocks & Acoustic Sealants

Versatile fireblocks for residential and other non-rated (Type V) construction. These products also act as a draftstop to help reduce air infiltration.

3M™ Fire Block Foam FB-Foam

Combines the high-speed application properties of foam and the long-lasting protection of caulk.

- Ready-to-use — no mixing required
- Expands up to 200% in volume to quickly and effectively seal openings
- Heat-resistant up to 240°F
- Tested to ASTM E 84 (modified) as a Type V Residential Fireblock
- Draftstop — helps reduce air infiltration
- Minimal shrinkage and sag-resistance help ensure longevity



3M™ Fire Block Sealant FB 136


Lightweight cementitious sealant with excellent adhesion. Bonds to concrete, metals, wood, plastic and cable jacketing.

- Heat-resistant up to 2,000°F
- Easy clean up with water
- No special handling — routine disposal
- Will not sag or run in vertical or overhead applications
- Formulated without halogens

3M™ Smoke and Sound Sealant SS 100

Economical, ready to use, gun-grade, elastomeric sealant that dries to form a monolithic flexible seal that helps prevent unwanted noise infiltration and mitigates the spread of smoke and toxic gas during a fire.

- ±10% movement capability
- An effective draftstop
- Re-enterable / repairable
- Sag-resistant formulation
- Excellent adhesion
- Paintable
- Cleans up with water





Construction Joint Firestop Solutions



SOUND BARRIER
STC 56
In STC 56-Rated
Wall Assembly

ELASTOMERIC
±50%
Movement
Capability

Available Colors:
■ Gray ■ Red

Whether you are a drywaller, carpenter, caulker, glazer or masonry contractor, one thing you know is construction joints move. When construction joints require firestopping, you need a tested product that can meet the demands of expanding and contracting joints day in and day out.

That's why 3M Fire Protection Products developed fire barrier sealants and sprays that meet the movement needs of head-of-wall, wall-to-wall and perimeter joints. These products undergo stringent building movement testing prior to firestop testing and are designed to meet the challenges of firestopping construction joints for many years.

3M™ FireDam™ Spray 200

This sprayable coating is a quick and easy method for firestopping fire rated construction joints, including: head-of-wall, wall-to-wall, floor-to-floor and perimeter joints.

- Up to 4-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Up to 2-hour fire ratings for through penetrations per ASTM E 814 (UL 1479)
- Elastomeric — forms a flexible seal with compression/extension of up to ±50% of nominal joint width
- High coverage rate reduces installation time
- Fast-drying, low-sag formula
- Applied with conventional airless spray equipment
- Paintable when cured
- Applied as 1/8 in. wet coating (per system details)
- Easy clean-up with water
- Available in 5 gallon pails

3M™ Fire Barrier Sealants, Putty and Sprays meet the intent of LEED® NC-EQ Credit 4.1 for Low-Emitting Materials. Adhesives and sealants contain <250 g/L VOC content (less H₂O and exempt solvents per SCAQMD Rule 1168).


Construction Joint Sprays & Sealants



3M™ Fire Barrier Sealant FD 150+

Economical firestop sealant for through-penetration and joint applications.

- Up to 4-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Up to 3-hour fire ratings for through penetrations per ASTM E 814 (UL 1479)
- Elastomeric — forms a flexible seal with compression/extension of up to $\pm 19\%$ of nominal joint width
- Easy installation, cleanup and disposal
- Formulated without halogens
- Sag-resistant



Available Colors:



Check UL directory. Not approved for use with CPVC pipes made using Noveon® resins.

3M™ Fire Barrier Water Tight Sealant 1000 NS

Non-slumping silicone firestop for wall and floor applications.

- Up to 3-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Up to 3-hour fire ratings for through penetrations per ASTM E 814 (UL 1479)
- Compression/extension recovery of $\pm 31\%$ of original joint width

3M™ Fire Barrier Water Tight Sealant 1003 SL



Self-leveling silicone firestop for floor applications.

- Up to 3-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Up to 3-hour fire ratings for through penetrations per ASTM E 814 (UL 1479)
- Compression/extension recovery of $\pm 31\%$ of original joint width

3M™ Fire Barrier Silicone Sealant 2000+

Bonds to most common construction materials to form a flexible firestop seal.

- Up to 4-hour fire ratings for joint systems per ASTM E 1966 (UL 2079)
- Up to 3-hour fire ratings for through penetrations per ASTM E 814 (UL 1479)
- Compression/extension recovery of $\pm 13\%$ of original joint width
- Superior adhesion
- Weather-resistant





Flexible Wrap

Fire Protection

Flexible solutions for the protection of grease ducts, ventilation air ducts, return air plenums, emergency circuits, structural steel and more. These flexible wrap products make installation easy, even around corners. Ideal for use in a wide variety of commercial and industrial applications.

FIRE BARRIER UP TO **2 HOUR** Fire Protection

FLEXIBLE WRAP GREASE & AIR DUCT Fire Protection

ICC **ES**™
ICC-ES ESR-1255

LISTED **OMEGA POINT LABORATORIES** US
Intertek
FIRE RESISTANT DUCT SEE INTERTEK DIRECTORY

LISTED **US**
Intertek
FIRE RESISTANT DUCT SEE INTERTEK DIRECTORY

NFPA 96

CLASSIFIED **UL**
BATTS AND BLANKETS FOR USE IN FIRE RESISTIVE DUCT ASSEMBLIES SEE UL FIRE RESISTANCE DIRECTORY 9069

LISTING SERVICE
CSFM
LISTING No. 2440-0941:112

3M™ Fire Barrier Duct Wrap 615+

Lightweight. Flexible. Protective. The only fire-rated duct wrap product you'll need to help protect grease and air ducts.

- Certified for grease ducts to ASTM E 2336 (including ASTM E 119 engulfment) in 2-layer systems. Certified for ventilation ducts to ISO 6944 in 1-layer systems and for other key life-safety duct applications.
- Also used to achieve T-ratings for metallic penetrations
- Tested and listed with UL and Intertek (OPL), meets the intent of IBC, IMC, UMC, NFPA and other key life safety codes
- Listed by California State Fire Marshal (Listing No. 2440-0941:5555)
- ICC-ES Evaluation Report ESR-1255
- Lightweight (6 lbs. per cu. ft.) and thin (1-1/2 in. — in accordance with ASTM C 892 tolerances) for easier application
- Heat-resistant (up to 2,192°F)
- Flexible for wrapping around corners and obstacles
- Non-asbestos wrap*
- Available in 1-1/2 in. x 24 in. x 25 ft. roll, or 1-1/2 in. x 48 in. x 25 ft. roll

* Made with non-biopersistent fibers, as defined by Nota Q of European Commission Directive 97/69/EU.

Flexible Wrap Firestop Systems

3M™ Fire Barrier Plenum Wrap 5A+

Lightweight wrap provides a flexible, non-combustible enclosure for cables and pipes in return air plenums.


- Strong, lightweight and flexible material for easy installation
- Tested to ASTM 84, NFPA 262 (UL 910) and UL 1887
- Foil encapsulated scrim
- Non-asbestos wrap
- Available in 1 in. x 24 in. x 50 ft. roll, or 1 in. x 48 in. x 25 ft. roll



3M™ Aluminum Foil Tape 425

Designed to perform in high temperatures.

- Used to seal cut edges of 3M™ Interam™ Endothermic Mat in order to complete total encapsulation
- Thermally-conductive, dead-soft aluminum backing combined with a transparent acrylic adhesive backing
- 4.6 mil (0.12mm) aluminum foil
- 4 in. x 60 yd. roll



3M™ FSK Facing Tape 3320

Conformable, easy-to-apply and temperature-resistant.

- Used to seal cut edges of 3M™ Fire Barrier Duct Wrap, 3M™ Fire Barrier Plenum Wrap and similar products in order to complete total encapsulation
- High-performance reinforced insulation tape (Foil/Scrim/Kraft)
- UL listed and mold-resistant
- Special acrylic adhesive works in both very cold and hot temperatures
- 3.89 in. x 50 yd. roll

Flexible Wrap Firestop Systems



3M™ Interam™ Endothermic Mat E-5A-4

Endothermic — releases chemically bound water to cool the assembly when exposed to high temperatures to protect structural steel, cable trays and circuits in conduits.

- Up to 4-hour protection for structural steel (ASTM E 119), up to 3-hour electrical circuit protection (ASTM E 1725) and up to 2-hour protection for wall opening membranes (UL 1479)*
- Outstanding performance in high-intensity fires, provides protection against large hydrocarbon pool fires in accordance with ASTM E 1529 (UL 1709)
- Made of a combination of organic/inorganic materials
- Outdoor durable**
- Available with a stainless-steel or aluminum backing
- Easily cuts to size and flexible — install in new applications or directly over existing fire protection
- 2/5 in. thick x 24-1/2 in. wide x 20 ft. long roll

* See system details for layering requirements.

** When covered with 0.010 in. stainless steel jacketing.



Wraps easily around existing structures. Multiple layers can be applied, allowing you to tailor the amount of fire protection required.











Approved for membrane penetration protection (e.g., electrical boxes and medical gas boxes).









Ordering Information

Visit www.3M.com/firestop for technical information, listed systems, training information and more or call 1-800-328-1687.

3M™ Fire Barrier Cast-In Devices and Accessories

Product	Product Number	Description	Shipping Wt./Carton	Billing UPC Number	Qty./Case	Qty./Pallet	Price Unit
Cast-In Devices for Plastic Pipes  	2PCID	2 in. Diameter	11.4 lbs.	000-51115-16536-8	12	420	Each
	3PCID	3 in. Diameter	17.0 lbs.	000-51115-16537-5	12	240	Each
	4PCID	4 in. Diameter	12.4 lbs.	000-51115-16538-2	6	180	Each
	6PCID	6 in. Diameter	8.7 lbs.	000-51115-16539-9	2	70	Each
Cast-In Devices for Metal Pipes  	2MCID	2 in. Diameter	11.6 lbs.	000-51115-16540-5	12	420	Each
	3MCID	3 in. Diameter	15.3 lbs.	000-51115-16541-2	12	240	Each
	4MCID	4 in. Diameter	10.5 lbs.	000-51115-16542-9	6	180	Each
	6MCID	6 in. Diameter	6.0 lbs.	000-51115-16543-6	2	70	Each
Product Accessories							
Metal Deck Adaptors 	2MDA	For use with 2PCID and 2MCID	5.2 lbs.	000-51115-16544-3	12	240	Each
	3MDA	For use with 3PCID and 3MCID	6.6 lbs.	000-51115-16545-0	12	240	Each
	4MDA	For use with 4PCID and 4MCID	7.0 lbs.	000-51115-16546-7	12	240	Each
	6MDA	For use with 6PCID and 6MCID	8.2 lbs.	000-51115-16547-4	12	192	Each
Height Adaptors 	2HA	For use with 2PCID and 2MCID	4.1 lbs.	000-51115-16548-1	12	420	Each
	3HA	For use with 3PCID and 3MCID	5.2 lbs.	000-51115-16549-8	12	240	Each
	4HA	For use with 4PCID and 4MCID	6.3 lbs.	000-51115-16550-4	12	240	Each
	6HA	For use with 6PCID and 6MCID	4.9 lbs.	000-51115-16551-1	12	144	Each
Tub Box Assembly 	3TB	For use with 2PCID and 2MCID	8.5 lbs.	500-51115-16586-8	6	108	Each
Aerator Adaptor 	4AA	For use with 4PCID and 4MCID	8.0 lbs.	500-51115-16589-9	12	288	Each

3M™ Fire Barrier Pass-through Devices and Accessories

Product	Product Number	Description	Shipping Wt./Carton	Billing UPC Number	Qty.	Price Unit
Square Device  	PT4SD	4 in. Square Re-enterable Firestop Device (Up to 4-hr Firestop)	13.6 lbs.	000-51115-16597-9	6/Cs	Each
Round Device  	PT2RD	2 in. Round Re-enterable Firestop Device (Up to 4-hr Firestop)	7.7 lbs.	000-51115-18773-5	6/Cs	Each
	PT4RD	4 in. Round Re-enterable Firestop Device (Up to 4-hr Firestop)	12.4 lbs.	000-51115-16598-6	6/Cs	Each
Product Accessories						
Single Mounting Brackets 	PT4SMB	For use with 4 in. Square Device	16.4 lbs.	000-51115-18752-0	24 Pair/Cs	Pair
	PT2RMB	For use with 2 in. Round Device	11.6 lbs.	000-51115-18774-2	24 Pair/Cs	Pair
	PT4RMB	For use with 4 in. Round Device	10.3 lbs.	000-51115-18754-4	24 Pair/Cs	Pair
Triplex Mounting Bracket 	PT4TMB	Gang up to three 4 in. Square Devices	29.1 lbs.	000-51115-18753-7	24 Pair/Cs	Pair
Sixplex Mounting Bracket 	PT4SSMB	Gang up to six 4 in. Square Devices	9.5 lbs.	000-51115-18777-3	6 Pair/Cs	Pair
Foam Plugs 	PT4SRP	For use with 4 in. Square Device	1.3 lbs.	000-51115-18794-0	24/Cs	Each
	PT2RRP	For use with 2 in. Round Device	0.4 lbs.	000-51115-18793-3	24/Cs	Each
	PT4RRP	For use with 4 in. Round Device	0.8 lbs.	000-51115-18791-9	24/Cs	Each

Ordering Information

Visit www.3M.com/firestop for technical information, listed systems, training information and more or call 1-800-328-1687.

3M™ Fire Barrier Rated Foam FIP 1-Step

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
FIP 1-Step FIRE BARRIER UP TO 2 HOURS SMOKE SEAL L RATED Meets All Leakage Requirements SOUND BARRIER STC 57 In STC 57-rated wall assembly TEMPERATURE T RATED UP TO 1 HOUR	Firestop Foam Up to 2-hr Penetration Firestop	12.85 oz.	Red	Cartridge	000-51115-54925-0	1/Cs	Each
HandyMax® HMS-J4C2	Manual Gun	—	—	Gun	000-51115-54927-4	1/Cs	Each
PowerMax® HPS-4C2	Battery-Powered Gun	—	—	Gun	000-51115-54928-1	1/Cs	Each
	Battery	—	—	Battery	000-51115-54930-4	1/Cs	Each

3M™ Fire Barrier Sealants

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
CP 25WB+ FIRE BARRIER UP TO 4 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 54 In STC 54-rated wall assembly	Up to 4-hr Penetration Firestop	10.1 oz.	Red	Tube	000-51115-11638-4	12/Cs	Each
	Up to 4-hr Penetration Firestop	20 oz.	Red	Sausage	000-51115-11642-1	10/Cs	Each
	Up to 4-hr Penetration Firestop	27 oz.	Red	Cartridge	000-51115-11641-4	6/Cs	Each
	Up to 4-hr Penetration Firestop	2 gal.	Red	Pail	000-51115-11639-1	1/Cs	Each
	Up to 4-hr Penetration Firestop	5 gal.	Red	Pail	000-51115-11640-7	1/Cs	Each
IC 15WB+ FIRE BARRIER UP TO 3 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 54 In STC 54-rated wall assembly	Up to 3-hr Penetration Firestop	10.1 oz.	Yellow	Tube	000-51115-16557-3	12/Cs	Each
	Up to 3-hr Penetration Firestop	20 oz.	Yellow	Sausage	000-51115-16560-3	10/Cs	Each
	Up to 3-hr Penetration Firestop	4.5 gal.	Yellow	Pail	000-51115-16558-0	1/Cs	Each
FD 150+ FIRE BARRIER UP TO 4 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 56 In STC 56-rated wall assembly ELASTOMERIC ±19% Movement Capability	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.	Blue	Tube	000-51115-11574-5	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.	Blue	Sausage	000-51115-11634-6	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.	Blue	Cartridge	000-51115-11602-5	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.	Blue	Pail	500-51115-11575-7	1/Cs	Each
FD 150+ FIRE BARRIER UP TO 4 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 56 In STC 56-rated wall assembly ELASTOMERIC ±19% Movement Capability	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.	Red	Tube	000-51115-18812-1	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.	Red	Sausage	000-51115-18810-7	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.	Red	Cartridge	000-51115-18811-4	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.	Red	Pail	000-51115-18813-8	1/Cs	Each
FD 150+ FIRE BARRIER UP TO 4 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 56 In STC 56-rated wall assembly ELASTOMERIC ±19% Movement Capability	Up to 3-hr Penetration/4-hr Joint Firestop	10.1 oz.	Grey	Tube	000-51115-16564-1	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	20 oz.	Grey	Sausage	000-51115-16567-2	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	28 oz.	Grey	Cartridge	000-51115-16566-5	6/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.	Grey	Pail	000-51115-16565-8	1/Cs	Each

3M™ Fire Barrier Water Tight Sealants (W-Rated)

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
3000 WT WATER TIGHT FIRE BARRIER UP TO 4 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 56 In STC 56-rated wall assembly WATER BARRIER UP TO 1 HOUR A.L. Water Leakage	Intumescent Silicone (Up to 4-hr Penetration Firestop)	10.1 oz.	Grey	Tube	000-51115-16593-1	12/Cs	Each
	Intumescent Silicone (Up to 4-hr Penetration Firestop)	20 oz.	Grey	Sausage	000-51115-18788-9	12/Cs	Each
	Intumescent Silicone (Up to 4-hr Penetration Firestop)	4.5 gal.	Grey	Pail	500-51115-16594-3	1/Cs	Each
1000 NS WATER TIGHT FIRE BARRIER UP TO 3 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 56 In STC 56-rated wall assembly ELASTOMERIC ±31% Movement Capability WATER BARRIER UP TO 1 HOUR A.L. Water Leakage	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	10.1 oz.	Grey	Tube	000-51115-11535-6	12/Cs	Each
	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	20 oz.	Grey	Sausage	000-51115-18790-2	12/Cs	Each
	Non-slump Silicone (Up to 3-hr Penetration/Joint Firestop)	4.5 gal.	Grey	Pail	500-51115-11537-5	1/Cs	Each
1003 SL WATER TIGHT FIRE BARRIER UP TO 3 HOUR Fire Protection SMOKE SEAL L RATED Meets Optional L Requirements SOUND BARRIER STC 56 In STC 56-rated wall assembly ELASTOMERIC ±31% Movement Capability WATER BARRIER UP TO 1 HOUR A.L. Water Leakage	Self-Leveling Silicone (Up to 3-hr Penetration/Joint Firestop)	10.1 oz.	Grey	Tube	000-51115-11538-7	12/Cs	Each
	Self-Leveling Silicone (Up to 3-hr Penetration/Joint Firestop)	20 oz.	Grey	Sausage	000-51115-18789-6	12/Cs	Each
	Self-Leveling Silicone (Up to 3-hr Penetration/Joint Firestop)	4.5 gal.	Grey	Pail	500-51115-11540-5	1/Cs	Each

3M™ Fire Barrier Silicone Sealant (water-resistant)

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
2000+ FIRE BARRIER SMOKE SEAL SOUND BARRIER ELASTOMERIC UP TO 4 HOUR Fire Protection L RIBED Meets Optional L Requirements 56 In STC 58-rated wall assembly ±13% Movement Capacity	Up to 3-hr Penetration/4-hr Joint Firestop	10.3 oz.		Tube	000-51115-11558-5	12/Cs	Each
	Up to 3-hr Penetration/4-hr Joint Firestop	4.5 gal.		Pail	500-51115-11559-7	1/Cs	Each

3M™ FireDam™ Spray 200

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
200 FIRE BARRIER SMOKE SEAL SOUND BARRIER ELASTOMERIC UP TO 4 HOUR Fire Protection L RIBED Meets Optional L Requirements 56 In STC 58-rated wall assembly ±50% Movement Capacity	Up to 2-hr Penetration/4-hr Joint Firestop	5.0 gal.		Pail	000-51115-18797-1	1/Cs	Each
	Up to 2-hr Penetration/4-hr Joint Firestop	5.0 gal.		Pail	000-51115-18798-8	1/Cs	Each

3M™ Fire Barrier Moldable Putty MP+

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
MPP-1+ WALL OPENING SMOKE SEAL SOUND BARRIER FIRE BARRIER UP TO 2 HOUR Fire Protection L RIBED Meets Optional L Requirements 52 In STC 58-rated wall assembly UP TO 4 HOUR Fire Protection	Moldable Putty Firestop—Pad (Up to 2-hr Wall Openings/ 4-hr Penetration Firestop)	4 in. x 8 in. (1/10 in. thick)		Pad	000-51115-16508-5	10/PK, 10 Pk/Cs	Each
	MPP-4S+ WALL OPENING SMOKE SEAL SOUND BARRIER FIRE BARRIER UP TO 2 HOUR Fire Protection L RIBED Meets Optional L Requirements 52 In STC 58-rated wall assembly UP TO 4 HOUR Fire Protection	Moldable Putty Firestop—Pad (Up to 2-hr Wall Openings/ 4-hr Penetration Firestop)	7 in. x 7 in. (1/10 in. thick)		Pad	000-51115-16509-2	20/Cs
MPP-5S+ WALL OPENING SMOKE SEAL SOUND BARRIER FIRE BARRIER UP TO 2 HOUR Fire Protection L RIBED Meets Optional L Requirements 52 In STC 58-rated wall assembly UP TO 4 HOUR Fire Protection		Moldable Putty Firestop—Pad (Up to 2-hr Wall Openings/ 4-hr Penetration Firestop)	9.5 in. x 9.5 in. (1/10 in. thick)		Pad	000-51115-16510-8	20/Cs
	MP+ FIRE BARRIER SMOKE SEAL SOUND BARRIER UP TO 4 HOUR Fire Protection L RIBED Meets Optional L Requirements 52 In STC 58-rated wall assembly	Moldable Putty Firestop—Stix in Tube (Up to 4-hr Penetration Firestop)	1.45 in. Dia. x 6 in. Approximate Dimension		Stix	000-51115-16561-0	12/Cs
MPS-2+ FIRE BARRIER SMOKE SEAL SOUND BARRIER UP TO 4 HOUR Fire Protection L RIBED Meets Optional L Requirements 52 In STC 58-rated wall assembly		Moldable Putty Firestop—Stix (Up to 4-hr Penetration Firestop)	1.5 in. Dia. x 11.5 in. Approximate Dimension		Stix	000-51115-16526-9	10/Cs

3M™ Fire Barrier Mortar

Product	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
Mortar (non load-bearing) FIRE BARRIER UP TO 3 HOUR Fire Protection	Dry Mix Mortar Firestop (Up to 3-hr Penetration Firestop)	28 lbs.		Pail	000-51115-54901-4	1/Cs	Each
	Dry Mix Mortar Firestop (Up to 3-hr Penetration Firestop)	44 lbs.		Bag	000-51115-54900-7	1/Cs	Each

3M™ Fire Barrier Putty Sleeve Kits


Product Number	Description	Sleeve Size	Shipping Wt./Case	Unit	Billing UPC Number	Qty.	Price Unit
Each Kit Includes: (1) Split Metal Sleeve; (2) Split Mounting Brackets; (1) Bag Screws; (2) Wall Labels							
DT 100 FIRE BARRIER UP TO 4 HOUR Fire Protection 	Re-enterable Firestop Kit (Up to 4-hr Penetration Firestop)	1 in. Dia.	1.7 lbs.	Kit	000-51115-18809-1	1/Cs	Each
	DT 200 FIRE BARRIER UP TO 4 HOUR Fire Protection 	Re-enterable Firestop Kit (Up to 4-hr Penetration Firestop)	2 in. Dia.	3.0 lbs.	Kit	000-51115-18808-4	1/Cs
DT 400 FIRE BARRIER UP TO 4 HOUR Fire Protection 		Re-enterable Firestop Kit (Up to 4-hr Penetration Firestop)	4 in. Dia.	6.9 lbs.	Kit	000-51115-18806-0	1/Cs

Ordering Information

Visit www.3M.com/firestop for technical information, listed systems, training information and more or call 1-800-328-1687.


3M™ Fire Barrier Composite Sheet CS-195+

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
CS-195+ (non load-bearing) Openings up to 36 sq. ft.	Composite Sheet (Up to 4-hr Penetration Firestop)	36 in. x 24 in. (.303 in. thick nominal)	Sheet	18.6 lbs.	000-51115-07220-8	1/Cs	Each
	Composite Sheet (Up to 4-hr Penetration Firestop)	28 in. x 52 in. (.303 in. thick nominal)	Sheet	32.0 lbs.	000-51115-08260-3	1/Cs	Each
	Composite Sheet (Up to 4-hr Penetration Firestop)	16 in. x 28 in. (.303 in. thick nominal)	Sheet	10.6 lbs.	000-51115-07437-0	1/Cs	Each
	Composite Sheet (Up to 4-hr Penetration Firestop)	36 in. x 41 in. (.303 in. thick nominal)	Sheet	34.9 lbs.	000-51115-07224-6	1/Cs	Each
	Composite Sheet (Up to 4-hr Penetration Firestop)	36 in. x 36 in. (.303 in. thick nominal)	Sheet	30.2 lbs.	000-51115-07222-2	1/Cs	Each



3M™ Fire Barrier Wrap Strips FS-195+

Product	Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
Wrap Strip FIRE BARRIER UP TO 4 HOUR Fire Protection	FS-195+	Intumescent wrap for most pipes and cables (Up to 4-hr Firestop)	2 in. x 24 in. (1/4 in. thick)	Strip	7.7 lbs.	000-51115-07115-7	10/Cs	Each




3M™ Fire Barrier Wrap Ultra GS

Product	Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
Ultra GS FIRE BARRIER UP TO 4 HOUR Fire Protection	ULTRA-GS-40	Intumescent wrap for insulated pipes, plastic pipes and combos (Up to 4-hr Firestop)	2 in. x 40 ft. (1/8 in. thick)	Roll	29.0 lbs.	000-51115-16507-8	5/Cs	Each



3M™ Fire Barrier Tuck-In Wrap Strips

Product	Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
Tuck-In Wrap Strips FIRE BARRIER UP TO 3 HOUR Fire Protection	WS 200	Intumescent wrap for 2 in. nominal plastic pipes (Up to 3-hr Firestop)	2-1/2 in. x 8-1/4 in. (3/16 in. thick)	Strip	3.9 lbs.	500-51115-18814-0	24/Cs	Each
	WS 300	Intumescent wrap for 3 in. nominal plastic pipes (Up to 3-hr Firestop)	2-1/2 in. x 11-1/2 in. (3/16 in. thick)	Strip	5.4 lbs.	500-51115-18815-7	24/Cs	Each
	WS 400	Intumescent wrap for 4 in. nominal plastic pipes (Up to 3-hr Firestop)	2-1/2 in. x 14-7/8 in. (3/16 in. thick)	Strip	7.0 lbs.	500-51115-18817-1	24/Cs	Each
	WS Roll	Intumescent wrap for plastic pipes (Up to 3-hr Firestop)	2-1/2 in. x 98.4 in. (3/16 in. thick)	Roll	15.9 lbs.	500-51115-18821-3	6/Cs	Roll




3M™ Fire Barrier Pillows




Product	Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
Firestop Pillows FIRE BARRIER UP TO 3 HOUR Fire Protection	FB249	Re-enterable pillows (Up to 3-hr Firestop)	2 in. x 4 in. x 9 in. (Small)	Pillow	12.5 lbs.	000-51115-16530-6	24/Cs	Each
	FB269	Re-enterable pillows (Up to 3-hr Firestop)	2 in. x 6 in. x 9 in. (Medium)	Pillow	12.5 lbs.	000-51115-16531-3	16/Cs	Each
	FB369	Re-enterable pillows (Up to 3-hr Firestop)	3 in. x 6 in. x 9 in. (Large)	Pillow	15.8 lbs.	000-51115-16532-0	20/Cs	Each



3M™ Fire Barrier Self-Locking Pillows

Product	Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
	FB249SL	Re-enterable, self-locking pillows (Up to 3-hr Firestop)	2 in. x 4 in. x 9 in. (Small)	Pillow	12.5 lbs.	500-51115-16578-3	24/Cs	Each
	FB269SL	Re-enterable, self-locking pillows (Up to 3-hr Firestop)	2 in. x 6 in. x 9 in. (Medium)	Pillow	12.5 lbs.	500-51115-16579-0	16/Cs	Each
	FB369SL	Re-enterable, self-locking pillows (Up to 3-hr Firestop)	3 in. x 6 in. x 9 in. (Large)	Pillow	15.8 lbs.	500-51115-16580-6	20/Cs	Each

3M™ Fire Barrier Plastic Pipe Devices

Product	Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
	Ultra PPD 1.5	Firestop for non-metallic pipes, cables and combos (Up to 3-hr Firestop)	1.5 in. Dia.	Device	3.9 lbs.	000-51115-08378-5	10/Cs	Each
	Ultra PPD 2.0	Firestop for non-metallic pipes, cables and combos (Up to 3-hr Firestop)	2 in. Dia.	Device	4.5 lbs.	000-51115-08379-2	10/Cs	Each
	Ultra PPD 3.0	Firestop for non-metallic pipes, cables and combos (Up to 3-hr Firestop)	3 in. Dia.	Device	7.5 lbs.	000-51115-08380-8	10/Cs	Each
	Ultra PPD 4.0	Firestop for non-metallic pipes, cables and combos (Up to 3-hr Firestop)	4 in. Dia.	Device	11.9 lbs.	000-51115-08381-5	10/Cs	Each
	PPD 6.0	Firestop for non-metallic pipes, cables and combos (Up to 3-hr Firestop)	6 in. Dia.	Device	20.2 lbs.	000-51115-08253-5	5/Cs	Each
Mounting Accessories								
	UF Anchor	Anchors for fast installation of plastic pipe devices	3/4 in. x 16 in.	Anchors	14.9 lbs.	000-51115-11530-1	400/Cs	Each



3M™ Fire Barrier RC-1 Restricting Collar

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
RC-1	Steel collar for use with Ultra GS or FS-195+ for firestopping up to 10 in. diameter plastic pipe	2 in. x 25 ft.	Roll	5.4 lbs.	000-54007-08324-5	1/Cs	Roll

3M™ Fire Barrier Packing Material PM 4

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
PM 4	Packing material for use in 3M through-penetration firestop systems	4 in. x 20.5 ft.	Roll	19.6 lbs.	000-51115-18764-3	5/Cs	Roll





3M™ Fire Block (for residential and Type V non-rated construction)

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
FB-136	Fireblock Sealant (Non-rated fire block/draftstop)	10.1 oz.	 Tube	16.0 lbs.	000-51115-16591-7	12/Cs	Each
FB-Foam	Expanding Fireblock Foam (Non-rated fire block/draftstop)	12.0 oz.	 Can	12.8 lbs.	000-51115-54907-6	12/Cs	Each


Ordering Information

Visit www.3M.com/firestop for technical information, listed systems, training information and more or call 1-800-328-1687.


3M™ Smoke and Sound Sealant SS 100

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
SS 100 	Elastomeric smoke, sound and draftstop sealant for use in non-fire-rated construction joints and through penetrations	20.0 oz.	<input type="checkbox"/>	 Sausage	000-51115-54923-6	12/Cs	Each
	Elastomeric smoke, sound and draftstop sealant for use in non-fire-rated construction joints and through penetrations	28.0 oz.	<input type="checkbox"/>	 Cartridge	000-51115-54922-9	6/Cs	Each
	Elastomeric smoke, sound and draftstop sealant for use in non-fire-rated construction joints and through penetrations	4.5 gal.	<input type="checkbox"/>	 Pail	000-51115-54924-3	1/Cs	Each

3M™ Interam™ Endothermic Mat E-5A-4


Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
E-5A-4 	Protective wrap for cable trays, conduits, wall opening membranes and more	24.5 in. x 20 ft. (408 in. thick)	Roll	86.1 lbs.	000-51115-54913-7	1/Cs	Roll

3M™ Fire Barrier Duct Wrap 615+


Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
615+ 	Space saving, flexible wrap for protection of air, grease, and chemical fume ducts	24 in. x 25 ft. (1.5 in. thick)	Roll	49.7 lbs.	000-51115-54905-2	1/Cs	Each
	Space saving, flexible wrap for protection of air, grease, and chemical fume ducts	48 in. x 25 ft. (1.5 in. thick)	Roll	99.4 lbs.	000-51115-54906-9	1/Cs	Each
	Collar for butted joint installations	6 in. x 25 ft. (1.5 in. thick)	Collar	49.7 lbs.	000-51115-18804-6	4/Cs	Each

Use two (2) layers for grease ducts per ASTM 2336. Use one (1) layer for air ducts per ISO 6994. Up to 2-hr T-ratings for through penetrations.


3M™ Fire Barrier Plenum Wrap 5A+

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
5A+ 	Flexible wrap for protection of plenum spaces	24 in. x 50 ft. (0.5 in. thick)	Roll	34.8 lbs.	000-51115-18802-2	1/Cs	Roll
	Flexible wrap for protection of plenum spaces	48 in. x 25 ft. (0.5 in. thick)	Roll	115.0 lbs.	000-51115-18805-3	2/Cs	Roll


3M™ Aluminum Foil Tape 425

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
425 	Seals cut edges of 3M™ Interam™ Endothermic Mat	4 in. x 60 yd. (4.6 mil thick)	Roll	6.4 lbs.	000-51138-95074-3	2/Cs	Roll

3M™ FSK Facing Tape 3320

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
3320 	Seals cut edges of 3M™ Fire Barrier Duct Wrap and Plenum Wrap	3.89 in. x 50 yd. (6.5 mil thick)	Roll	18.0 lbs.	000-51115-00705-7	2/Cs	Roll

3M™ Firestop Identification Labels

Product Number	Description	Size	Unit	Shipping Wt./Case	Billing UPC Number	Qty.	Price Unit
WRNGLBL 	Adhesive-backed label used to identify through penetration or joint firestop systems in fire-rated construction. 250 labels per roll	3 in. x 5 in.	Roll	4.97 lbs.	000-51115-54917-5	4/Cs	Roll

Value Beyond the Products

Online tools available at
www.3M.com/firestop

The 3M Fire Protection Product website is designed to enhance our technical and sales support by providing users easy access to critical information needed in the construction and maintenance of buildings requiring passive fire protection. In addition to a wealth of product and technical information, here are some value-added tools that can be accessed from the 3M Fire Protection website:



3M™ System Selector

Helps you quickly navigate through our extensive library of tested and listed systems to provide a short list of suitable systems for a specific application.

3M™ Submittal Wizard

Allows users to access, select and combine documents from multiple applications on the 3M Fire Protection website. Selected documents can be combined into a single pdf for user's submittal.

Training

3M offers fire protection training online or at our UL certified test center. Our website provides information on upcoming courses as well as registration for e-Train. e-Train is the 3M Fire Protection online learning management system designed to provide users with general firestopping information and trade-specific installation details.

3M™ Firestop Management System

This web-based application is designed to help existing facilities monitor their fire barrier management system. With specific functionality to help healthcare facilities pass Joint Commission and other key life safety inspections, key features include contractor management (e.g. issue permits, monitor access), firestop system management down to every floor or wall, document retention including life safety plans and installation photos, and report generation (e.g. system inventory or contractor status).

Contact Your Local Distributor or 3M Fire Protection Sales Representative for More Information

www.3M.com/firestop

- For distributors near you, click **“WHERE TO BUY”**.
- For your local sales representative, click **“CONTACT US”**.
- Can't find what you are looking for? Call us at **1-800-328-1687**.



**3M Building and Commercial
Services Division**

3M Center
Building 223-2N-21
St. Paul, MN 55144-1000
1-800-328-1687
www.3M.com/firestop

Please recycle. Printed in U.S.A.
© 3M 2013. All rights reserved.
98-0213-4364-9 Rev. D.

Warranty and Limited Remedy. 3M warrants that each 3M Fire Protection Product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability. Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

The FBC® System Compatible logo indicates that a 3M product has been tested and is monitored on an on going basis to assure chemical compatibility with FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings. FBC is a registered trademark and FlowGuard Gold, Blazemaster and Corzan are trademarks of Lubrizol Advanced Materials, Inc. © Lubrizol Advanced Materials, Inc. 2013. All rights reserved.

3M, Interam and FireDam are trademarks of 3M. Used under license in Canada. NFPA is a trademark of the National Fire Protection Association. HandyMax and PowerMax are registered trademarks of Soraton SA. All other trademarks are the property of their respective owners.