

PROWALL II

Anti-graffiti protective coating



Product description:

PROWALL II is a solvent-free special coating on the basis of natural waxes. Walls and facades are reliably protected against graffiti and other soiling.

PROWALL II is a one-component-system and is therefore very easy to apply. The work involved in cleaning soiled surfaces is reduced to a minimum and is therefore very effective and inexpensive. Graffiti can be easily removed from **PROWALL**-protected surfaces with a high pressure cleaner. No additional chemical cleaning agents are necessary. **PROWALL II** is practically invisible after drying and also acts water repelling.

Fields of Application:

Facades and walls, natural or artificial stone, brick, plaster, concrete, metal (painted and unpainted), glass, plastic etc. Suitable for both indoor and outdoor applications.

Characteristics:

- special protective coating, based on natural waxes
- reliably protects facades, noise protection walls, garages, underpasses etc. against graffiti and other soiling. Valuable structures are preserved and maintained
- invisible
- water-repellent
- UV-resistant
- solvent-free
- has been performing excellently in practice for many years.

Advantages:

- one-component system and is therefore fast and easily to use
- protects reliably against graffiti and similar soiling
- the breathability of the treated surface is maintained (only slightly reduced)
- no additional chemicals are needed to clean the protected surface. Graffiti can be easily removed with a high-pressure cleaner.
- resistant to weathering and UV-resistant (BAUTEST test certificate no. A 3547/90)
- due to the large number of influencing factors, it is not possible to make an exact statement about the expected durability. However according to expert opinions the BAUTEST test certificate A3547/90 is equivalent to a minimum of 10 years

Instructions for Use:

PROWALL II should be applied with a brush, a roller or a sprayer to the dry, clean, frost-free and dust-free surface. An immediate repeated application (wet in wet) may be necessary, especially on absorbent surfaces.

Construction joints, which are to be subsequently sealed/grouted, should be covered/masked before **PROWALL II** is applied, as otherwise this may lead to a reduction of adhesion. Graffiti can be easily removed from the protected surfaces with a high-pressure cleaner or a steam cleaner. It may be necessary to use hot water for cleaning, depending on the type and composition of the graffiti paint. No additional chemicals are required. The **PROWALL II** protection must be renewed after every cleaning.

PROWALL II is not hazardous, is solvent-free and can therefore also be applied on coated or painted surfaces.

Not for use by temperatures below +10°C .

Pilot tests are always necessary.

Consumption (non-binding, estimated values):

- By plaster, limestone, roughened concrete and similarly absorbent surfaces: approx. 250-300 ml/sqm
- By fair-faced concrete: approx. 150-200 ml/sqm
- By painted surfaces: approx. 150ml/sqm
- By metal, glass and similar smooth surfaces: approx. 100 ml/sqm

Please note, that is always necessary to carry out pilot tests which realistically correspond to the planned production process and the application procedure. When applying to outdoor surfaces, testing should also take the natural weathering into account and allow for an adequate period of observation.

Consumption:
Depending on the absorbency of the surface, approx. 100-300 ml/sqm

Packaging:
10-30-200-1000 l drums/barrels/containers

Storage:
Store frost-free. Can be stored for approx.12 months in original closed containers

PROWALL II

Anti-graffiti protective coating

Application examples:



Application of **PROWALL**, e.g. with a roller.



Don't forget to renew the **PROWALL**-protection after cleaning the surface!



If the protected surface is soiled with graffiti: clean surface with a high pressure cleaner.

Sample text for invitations to tender:

For anti-graffiti protection

Protect surfaces, e.g. facades/walls against graffiti and similar soiling with

PROWALL from HEBAU GmbH,
or equivalent product

Application: see "Instructions for Use"

Consumption: depending on absorbency of the surface, approx. 100 - 300 ml/sqm

Surface in sqm:

Legal notice:

The technical information contained herein, in particular relating to the function, use and handling of our products, is given to the best of our knowledge and is based on our present knowledge and experience of the products when appropriately stored and handled, and applied under normal conditions in accordance with the standard fields of application, as described in page 1. Due to the large variety of possible use and application scenarios, this data sheet raises no claim to completeness, but is solely intended to provide a non-binding decision support, which needs to be reconfirmed by the end-user through pilot tests. Pilot tests are always necessary and should be carried out following the advice given in the current Product Data Sheet and under realistic practical conditions, i.e. conditions must realistically correspond to the planned production process and application procedure. Case-related acquired knowledge is not directly transferable to similar applications. Product specifications are subject to alterations without notice.

Only the most recent issue of the Product Data Sheet is valid, which will be supplied on request or can be found on our website under www.hebau.de.

We guarantee for the perfect quality of our material according to our specifications. We do not take any liability resp. warranty for the desired end result, as we solely act as supplier of the products and the application of the products and other influencing factors are beyond our control and our field of responsibility.

Usual precautions and actions when handling chemicals should be observed (e.g. no eating, drinking, or smoking at the place of work).

Additional instructions, which can be found on the corresponding product labelling or in the Safety Data Sheet, must be observed. If you do not have a copy of the current Safety Data Sheet, we will be pleased to send you one.

Our General Terms and Conditions apply. This information is valid for professional users. Our products are not recommended for private end-users. 24.11.2015